

GABRIELLA-45-S

~9° spot beam with holder


TECHNICAL SPECIFICATIONS:

Dimensions	Ø 45.0 mm
Height	28.9 mm
Fastening	pin, screw
Colour	black
Box size	
Box weight	0 kg
Quantity in Box	405 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:


Component	Type	Material	Colour
GABRIELLA-45-S	Lens	PMMA	clear
GABRIELLA-45-HLD	Holder	PC	black




PHOTOMETRIC DATA (MEASURED):





LED XM-L RGB
 FWHM 12.0°
 Efficiency 87 %
 Peak intensity 17.000 cd/lm
 Required components:





LED LUXEON CZ RGBW
 FWHM 14.0°
 Efficiency 88 %
 Peak intensity 11.400 cd/lm
 Required components:



LED SBM-40-RGBW
 FWHM 10.0°
 Efficiency 90 %
 Peak intensity 24.000 cd/lm
 Required components:




LED DMC E17A RGBW
 FWHM 13.0°
 Efficiency 91 %
 Peak intensity 11.000 cd/lm
 Required components:



PHOTOMETRIC DATA (MEASURED):


OSRAM
Opto Semiconductors

LED Oslon Square EC
FWHM 10.0°
Efficiency 88 %
Peak intensity 21.300 cd/lm
Required components:



OSRAM
Opto Semiconductors


LED OSTAR Stage (S2WN)
FWHM 10.0°
Efficiency 87 %
Peak intensity 24.000 cd/lm
Required components:



PHOTOMETRIC DATA (SIMULATED):


CITIZEN

LED PSL440
 FWHM 11.0°
 Efficiency 93 %
 Peak intensity 20.200 cd/lm
 Required components:




CITIZEN

LED PSL445
 FWHM 15.0°
 Efficiency 91 %
 Peak intensity 10.211 cd/lm
 Required components:




CREE

LED XHP50
 FWHM 14.0°
 Efficiency 92 %
 Peak intensity 13.800 cd/lm
 Required components:



CREE


LED XHP50.2
 FWHM 13.0°
 Efficiency 91 %
 Peak intensity 14.250 cd/lm
 Required components:




PHOTOMETRIC DATA (SIMULATED):




LED XHP70
FWHM 18.0°
Efficiency 90 %
Peak intensity 8.900 cd/lm
Required components:




LED LZ4 RGBW Power (LZ4-04MDPB)
FWHM 10.0°
Efficiency 92 %
Peak intensity 28.410 cd/lm
Required components:



LED LUXEON C RGBW
FWHM 15.0°
Efficiency 85 %
Peak intensity 13.555 cd/lm
Required components:




LED OSTAR Stage (S2WP)
FWHM 11.0°
Efficiency 92 %
Peak intensity 22.794 cd/lm
Required components:



PHOTOMETRIC DATA (SIMULATED):

OSRAM
Opto Semiconductors

LED Ostar-SMT RGB
FWHM 10.0°
Efficiency 92 %
Peak intensity 31.649 cd/lm
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)