



Part Number: 35618

Hook-Up/Lead Wire UL AWM Style 3173 - XL-DUR®, (1) 18 AWG (16x30) TC, XLPE, 600V, 125°C

Request Sample
 Requ

Product Description

One 18 AWG stranded (16x30) tinned copper conductor, cross-linked polyethylene insulation.

Technical Specifications

Physical Characteristics (Overall)

Conductor AWG Stranding Material No. of Conductors 18 16x30 TC - Tinned Copper 1 Conductor Count: 1 Conductor Size: 18 AWG

Insulation

| Material | Nominal Diameter | Nominal Wall Thickness | Min. Average Wall Thickness |
|----------------------------------|------------------|------------------------|-----------------------------|
| XLPE - Cross Linked Polyethylene | 0.109 in | 0.0315 in | 0.03 in |

Outer Jacket Material

Material No Jacket

Electrical Characteristics

Conductor DCR



Shielding: Unshielded

Current

| Element | Max. Recommended Current [A] |
|--|------------------------------|
| Single conductor in free air @ ambient 30C | 22 amps |

Voltage

UL Voltage Rating 600 V RMS

Temperature Range

| UL Temp Rating: | 125°C |
|-----------------|-------|
|-----------------|-------|

Mechanical Characteristics

| Bulk Cable Weight: | 10 lbs/1000ft |
|--------------------|---------------|

Standards

| UL AWM Style: | 3173 |
|-------------------------|--------------|
| CSA Rating: | 600 V, 125°C |
| CSA Type: | CL1251 |
| Military Specification: | N/A |

Applicable Environmental and Other Programs

| EU Directive 2000/53/EC (ELV): | Yes |
|---------------------------------------|-------------------------------|
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU: | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2004-07-01 |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Flammability, LS0H, Toxicity Testing

| UL voltage rating: | 600 V RMS |
|--------------------|-----------|

Plenum/Non-Plenum

| Plenum (Y/N): | No | |
|---------------|----|--|

Part Number

Variants

| Item # | Color | Footnote |
|---------------|-------------|----------|
| 35618 010500 | Black | F |
| 35618 0105000 | Black | CIUZ |
| 35618 0135000 | Blue, Dark | CIUZ |
| 35618 0065000 | Blue, Light | CIUZ |
| 35618 0015000 | Brown | CIUZ |
| 35618 0085000 | Gray | CIUZ |
| 35618 0055000 | Green, Dark | CIUZ |
| 35618 0035000 | Orange | CIUZ |
| 35618 0125000 | Pink | CIUZ |
| 35618 002500 | Red | F |
| 35618 0025000 | Red | CIUZ |
| 35618 0075000 | Violet | CIUZ |
| 35618 0095000 | White | CIUZ |
| 35618 004500 | Yellow | F |
| 35618 0045000 | Yellow | CIUZ |

| Footnote: | C - CRATE REEL PUT-UP. |
|-----------|--|
| Footnote: | I - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 200'. |
| Footnote: | U - TOPCOAT ADDERS ON STOCK SOLID COLORS. MINIMUM ORDER 10,000' PER COLOR COMBINATION. (SEE TOPCOAT ADDER TABLE) |
| Footnote: | Z - FINAL PUT-UP MAY VARY (= OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN. |
| Footnote: | F - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 50°. |

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.